



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


CERTIFIED COPY OF
PRIORITY DOCUMENT

Signed *Am. Brown*

Dated 16 July 2004

BEST AVAILABLE COPY

THIS PAGE BLANK (USPTO)



1/77

07MAR03 E/90345-1 D00389
P01/7700 0.00-0305164.6**Request for grant of a patent***(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)***The Patent Office**Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

P17313GB-NF/SJP/jsd

2. Patent application number

(The Patent Office will fill in this part)

06 MAR 2003

0305164.6

3. Full name, address and postcode of the or of each applicant *(underline all surnames)*Autoliv Development AB,
Patent Department Sweden,
S-447 83 VARGARDA,
Sweden.Patents ADP number *(if you know it)*

If the applicant is a corporate body, give the country/state of its incorporation

Sweden

321018006

4. Title of the invention

"Improvements in or Relating to a Safety Device"

5. Name of your agent *(if you have one)*

Forrester Ketley & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*Forrester House
52 Bounds Green Road
London
N11 2EYPatents ADP number *(if you know it)*

133001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number

Country

Priority application number
*(if you know it)*Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
*(day / month / year)*8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

| | |
|-------------|-------------|
| Description | 10 |
| Claim(s) | 3 |
| Abstract | 1 <i>DL</i> |
| Drawing(s) | 4 <i>+4</i> |

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) 3 ✓

Request for preliminary examination and search (*Patents Form 9/77*) 1 ✓

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. ☒ We request the grant of a patent on the basis of this application.

Signature *Forrester Ketley & Co.* Date 6 March 2003
Forrester Ketley & Co.

12. Name and daytime telephone number of person to contact in the United Kingdom
(020) 8889 6622 FRANKLAND, Nigel H.

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.


Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.



7/77

**Statement of inventorship and of
right to grant of a patent**



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

| | | | | | | |
|---|---|-----------|-----------|------|----------------------------|---------------|
| 1. Your reference | P17313GB-NF/SJP/jsd | | | | | |
| 2. Patent application number <i>(if you know it)</i> | 06 MAR 2003 | 0305164.6 | | | | |
| 3. Full name of the or of each applicant | Autoliv Development AB | | | | | |
| 4. Title of the invention | "Improvements in or Relating to a Safety Device" | | | | | |
| 5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent | By Agreement | | | | | |
| 6. How many, if any, additional Patents Forms 7/77 are attached to this form? <i>(see note (c))</i> | None | | | | | |
| 7. | <p><i>I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.</i></p> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Signature</td> <td style="text-align: center;">Date</td> </tr> <tr> <td style="text-align: center;"> Forrester Ketley & Co. </td> <td style="text-align: center;">6 March, 2003</td> </tr> </table> | | Signature | Date | Forrester Ketley & Co. | 6 March, 2003 |
| Signature | Date | | | | | |
| Forrester Ketley & Co. | 6 March, 2003 | | | | | |
| 8. Name and daytime telephone number of person to contact in the United Kingdom | FRANKLAND, Nigel H. (020) 8889 6622 | | | | | |

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

QVINT, Peter,
Egnahemsgatan 16,
447 30 VARGARDA,
Sweden.

174599001

Patents ADP number (if you know it):

KARLIN, Mats,
Kungsgatan 15,
447 33 VARGARDA,
Sweden.

2257321002

Patents ADP number (if you know it):

Reminder

Have you signed the form?

Patents ADP number (if you know it):

PATENTS ACT 1977

P17313GB-NF/jsd

5 DESCRIPTION OF INVENTION

“IMPROVEMENTS IN OR RELATING TO A SAFETY DEVICE”

10

THE PRESENT INVENTION relates to a safety device.

15

It has been proposed to provide various forms of safety device to provide protection for an occupant of a vehicle in the event that an accident should occur. For example, various types of air-bag have been proposed which, depending upon their design, may occupy many different positions within a vehicle relative to a driver. When an air-bag is to be deployed, a gas generator is actuated which generates gas which serves to inflate the air-bag.

20

In some cases it is desirable for the pressure in the air-bag to be controlled and/or for the air-bag to be “vented”, especially if the occupant has a weight which is not typical, either being relatively heavy or being relatively light, or, alternatively, if the occupant is “out of position” (for example leaning forwardly).

25

Various proposals have been made for mechanisms to ventilate an air-bag including controlled valves, burst discs and tear-seams which initially seal an outlet air vent. Sophisticated arrangements may include elements such as pressure sensors and/or control units to determine the weight and the position of

an occupant and to control the opening of a gas exhaust valve in an optimal manner.

5 However, there is a requirement for a simple device to control the ventilation of an air-bag which can be used in a flexible manner to provide ventilation at different positions within an air-bag.

Other safety devices also rely on generated gas, such as pre-tensioners, and there is a requirement for a mechanism that may be utilised to control the
10 operation of such safety devices.

According to a first aspect of the present invention, there is provided a safety device in the form of a releasable clip, the releasable clip having a first elongate main gripping element, and a second elongate moveable gripping
15 element, the main gripping element having a retaining element to retain one end of the moveable gripping element; there being an arrangement to retain the other end of the moveable gripping element in a predetermined position such that the clip may grip a fabric tube or the like between the main gripping element and the moveable gripping element; a mechanism being provided
20 which responds to a supply signal to move said other end of the moveable gripping element to release the grip.

According to another aspect of the present invention, there is provided a safety device configured to be actuated by the supply of gas, the safety device
25 incorporating an outlet vent pipe, the outlet vent pipe being sealed by a releasable clip, the releasable clip having a first elongate main gripping element, and a second elongate moveable gripping element, the main gripping element having a retaining element to retain one end of the moveable gripping element; there being an arrangement to retain the other end of the moveable

gripping element in a predetermined position such that the clip may grip the outlet vent pipe or the like between the main gripping element and the moveable gripping element; a mechanism being provided which responds to a supply signal to move said other end of the moveable gripping element to
5 release the grip.

Preferably, the safety device is an air-bag.

Advantageously, the safety device is a pretensioner.
10

Conveniently, a plurality of said releasable clips are provided, each clip being associated with a respective outlet hose.

Preferably, the releasable clip incorporates a spring initially held in a compressed state and released in response to said signal so as to move the said
15 other end of the moveable retaining element.

Advantageously, the main gripping element is in the form of a cylinder, and said other end of the elongate moveable gripping element is configured to
20 fit over or within the cylinder; there being a mechanism to supply gas to the interior of the cylinder in response to said signal to move the said other end of the moveable gripping element.

Conveniently, said other end of the moveable gripping element is
25 constituted by a piston retained within the cylinder.

Preferably, said other end of the moveable gripping element comprises a closure cap dimensioned to close an open end of the cylinder.

Advantageously, the source of gas is a pyrotechnic squib.

Alternatively, the source of gas is a source of compressed gas.

5

Preferably, the moveable gripping element is provided with an elongate cylindrical gripping portion, one end of which is engaged in a retaining lug provided on the main gripping element.

10

Advantageously, the main gripping element is in the form of a cylindrical housing, and the moveable gripping element has inclined resiliently mounted walls to engage the exterior of the cylindrical main gripping element.

15

In order that the invention may be more readily understood, and so that further features thereof may be appreciated, the invention will now be described, by way of example, with reference to the accompanying drawings in which:

20

FIGURE 1 is a perspective view of a pyrotechnic clip unit,

FIGURE 2 is an end view of the unit of Figure 1,

25

FIGURE 3 is a sectional view, on an enlarged scale, taken on the line A-A of Figure 2,

FIGURE 4 is a view showing the clip unit of Figures 1 to 3 mounted on an outlet duct of an air-bag,

FIGURE 5 is a view corresponding to Figure 4 showing the clip unit when released,

FIGURE 6 is a view illustrating an air-bag in a motor vehicle provided with a pyrotechnic clip unit of the type described above during inflation of an air-bag,

FIGURE 7 is a view corresponding to Figure 6 showing the clip unit when released, and

10

FIGURE 8 is a perspective view of an alternative form of clip unit in accordance with the invention.

Turning initially to Figures 1 to 3 of the accompanying drawings, a pyrotechnic clip unit 1 is illustrated, the pyrotechnic clip unit being configured so that, when in use, it may close an outlet hose or duct, formed of a material such as fabric, forming part of an air-bag or forming part of another safety device.

The clip 1 comprises an elongate hollow cylindrical housing 2 which forms a main gripping element, one end of the housing being provided with an integral deflected retaining bracket 3 in the form of a lug. The retaining bracket 3 defines a "U"-shaped slot 4 which opens into one side edge of the retaining bracket 3.

25

The end of the hollow cylindrical housing 2 provided with the retaining bracket 3 receives a pyrotechnic squib 5 which is held by a crimp 6 as illustrated most clearly in Figure 3. The pyrotechnic squib 5 contains a pyrotechnic charge and is associated with two electrodes 7 which are accessible

from the open end of the housing 2. A plug may be connected to the electrodes 7. When a current is passed between the electrodes 7, the pyrotechnic squib 5 is ignited to generate a substantial quantity of gas.

5 A moveable gripping element 8 is provided, the gripping element 8 including an elongate cylindrical gripping section 9 having a terminal region 10 configured to be received within the "U"-shaped slot 4 formed in the retaining bracket 3. The other end of the gripping section 9 is provided with a 180° bend 11 which connects the gripping section 9 to a piston 12 which is dimensioned to
10 be received, as a sliding fit, within the hollow tube 2. The piston 12 may have a semi-spherical head so as to provide a substantially sealing fit even if the piston is not precisely aligned with the longitudinal axis of the hollow cylindrical housing 2.

15 Referring now to Figure 4, the clip 1 of Figures 1 to 3 is shown in position on the terminal part of a tube 13 which may be a fabric tube extending from an air-bag to constitute a gas vent, or which may be a fabric tube extending from part of some other safety device which is deployed by the generation of gas.

20

It will be understood that the terminal part of the tube 13 has been located in position generally between the cylindrical housing 2 and the gripping section 9 of the moveable gripping element 8. The terminal part 10 of the gripping section 9 has been manipulated to be received within the "U"-shaped
25 slot 4 of the retaining bracket 3, thus firmly trapping the fabric of the tube 13 between the gripping section 9 of the moveable gripping element 8, and the outer surface of the cylindrical housing 2. The clip 1 thus forms a substantially air-tight seal at the end of the tube 13.

Should an appropriate electrical signal be supplied to the electrodes 7, the pyrotechnic squib 5 will be ignited generating a substantial quantity of gas within the cylinder 2. The gas will act on the piston 12 moving the piston 12 axially of the cylindrical housing 2, and thus withdrawing the terminal part 10 of the moveable gripping element 8 from the "U"-shaped slot 4 formed in the retaining bracket 3. The moveable gripping element 8 thus moves relative to the main gripping element formed by the housing 2. Indeed, the entire gripping element 8 may, as shown in Figure 5, become totally separated from the cylindrical housing 2. Thus the tube 13 is no longer retained in a sealed condition and gas may escape from the air-bag through the tube 13.

It is to be understood that a number of clips of the type described above may be provided on a typical air-bag at a number of different positions, and the actuation of the clips may be controlled by an appropriate control arrangement associated with appropriate sensors. Consequently a number of the described clips may be provided on various gas ducts 13 forming part of a single air-bag, and one or more of the clips may be released. If more than one clip is released, the clips may be released at appropriate times during an accident situation, in dependence upon the particular circumstances of an accident involving a vehicle in which the air-bag is mounted.

Referring now to Figures 6 and 7, merely by way of an example, an air-bag 20 in the form of a so-called "inflatable curtain" is illustrated, the air-bag 20 having a forwardly extending restraining strap 21 which is in the form of a hollow tube in fluid communication with the invention of the main part of the air-bag 20. The free end of the tube is received within a clip 1 as described above, the cylindrical housing 2 of the clip 1 being securely fastened to the

"A"-Post 22 of the illustrated vehicle. Thus the clip 1 seals the tubular strap 21 and also anchors the end of the strap in position.

5 In ordinary deployment of the inflatable curtain, gas will be injected into the inflatable parts of the inflatable curtain, but will not be able to escape through the tubular strap 21, because the tubular strap 21 is maintained closed by the action of the clip 1. The clip 1 also holds the tubular restraining strap 21 securely in position.

10 Should a particular set of circumstances arise, in which it is appropriate to release the restraining strap 21 and deflate the inflatable curtain, the clip 1 may be released, in the manner described above, by actuating the pyrotechnic squib 5, as shown in Figure 7, thus releasing the end of the tubular restraining strap 21 permitting gas to escape from the inflated interior of the inflatable
15 curtain 20 through the thus released tubular strap 21, as shown in Figure 7.

Whilst the invention has been described above with reference to one form of releasable clip, Figure 8 illustrates a modified form of releasable clip. The clip of Figure 8 includes a hollow tubular housing 30 forming a main gripping element and having, at one end, a deflected retaining bracket 31 in the
20 form of a lug which defines a square aperture 32. Received within that end of the tubular housing 31 is a squib 33 corresponding to the squib 5 as described above.

25 Associated with the housing 30 is a moveable gripping element 34. The moveable gripping element 34 is formed of a pressed plate, the pressed plate defining two inwardly directed opposed resiliently mounted walls 35,36 having a substantially "V" configuration, the lower ends of the walls being interconnected by a "U"-shaped trough 37. At one end, the trough 37 extends

axially to form a projection 38. The projection 38 is dimensioned to be received within the square aperture 32 in the retaining bracket 31. At the other end, the trough 37 carries an upstanding support 39 which extends up between the walls 35, 36, and which carries a closure cap 40 dimensioned to fit over and close, in a sealing manner, the open end of the housing 30 remote from the squib 33.

It is to be appreciated that the moveable gripping element 34 is so configured that when the projection 38 of the trough 37 is received within the aperture 32, the closure cap 40 sealingly closes the end of the housing 30 remote from the squib 33, and the walls 35, 36, due to their own resilient mounting, are biased against the exterior of the housing 30.

It will be appreciated that the clip may be mounted on a hose, equivalent to the tube 13 as shown in Figures 4 and 5, with the hose being partly wrapped around the cylindrical housing 30, and with the hose being gripped by the two resiliently biased walls 35, 36. The engagement of the projection 38 within the aperture 32, and the engagement of the sealing cap 40 with the end of the housing 30 ensures that the moveable gripping element 34 remains in position. Should, however, an electric charge be applied to the pyrotechnic squib 5, a substantial quantity of gas will be injected into the interior of the hollow housing 30, thus driving the sealing cap 40 away from the end of the housing 30 remote from the squib 33, consequently serving to withdraw the projection 38 from the aperture 32, and releasing the moveable gripping element 34 from the housing 30.

Whilst the invention has been described with specific reference to clips in which gas is generated by a pyrotechnic squib in response to a signal, it is to be understood that in a modified embodiment, instead of using the squib, a

source of compressed gas that is opened by a signal may be used, or even a clip that includes a spring which is retained in a compressed state and released in response to a signal to release the clip.

- 5 In the present Specification "comprises" means "includes or consists of" and "comprising" means "including or consisting of".

- 10 The features disclosed in the foregoing description, or the following Claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS:

1. A safety device in the form of a releasable clip, the releasable clip
5 having a first elongate main gripping element, and a second elongate moveable
gripping element, the main gripping element having a retaining element to
retain one end of the moveable gripping element; there being an arrangement to
retain the other end of the moveable gripping element in a predetermined
position such that the clip may grip a fabric tube or the like between the main
10 gripping element and the moveable gripping element; a mechanism being
provided which responds to a supply signal to move said other end of the
moveable gripping element to release the grip.
2. A safety device configured to be actuated by the supply of gas, the safety
15 device incorporating an outlet vent pipe, the outlet vent pipe being sealed by a
releasable clip, the releasable clip having a first elongate main gripping
element, and a second elongate moveable gripping element, the main gripping
element having a retaining element to retain one end of the moveable gripping
element; there being an arrangement to retain the other end of the moveable
20 gripping element in a predetermined position such that the clip may grip the
outlet vent pipe or the like between the main gripping element and the
moveable gripping element; a mechanism being provided which responds to a
supply signal to move said other end of the moveable gripping element to
release the grip.
- 25
3. A safety device according to Claim 2 wherein the safety device is an air-
bag.

4. A safety device according to Claim 2 wherein the safety device is a pretensioner.
5. A safety device according to Claim 2, 3 or 4 wherein a plurality of said
5 releasable clips are provided, each clip being associated with a respective outlet hose.
6. A safety device according to any one of the preceding Claims wherein
10 the releasable clip incorporates a spring initially held in a compressed state and released in response to said signal so as to move the said other end of the moveable retaining element.
7. A safety device according to any one of Claims 1 to 5 wherein the main
15 gripping element is in the form of a cylinder, and said other end of the elongate moveable gripping element is configured to fit over or within the cylinder; there being a mechanism to supply gas to the interior of the cylinder in response to said signal to move the said other end of the moveable gripping element.
8. A safety device according to Claim 7 wherein said other end of the
20 moveable gripping element is constituted by a piston retained within the cylinder.
9. A safety device according to Claim 7 wherein said other end of the
25 moveable gripping element comprises a closure cap dimensioned to close an open end of the cylinder.
10. A safety device according to any one of Claims 7 to 9 wherein the source of gas is a pyrotechnic squib.

11. A safety device according to any one of Claims 7 to 9 wherein the source of gas is a source of compressed gas.

5 12. A safety device according to any one of the preceding Claims wherein the moveable gripping element is provided with an elongate cylindrical gripping portion, one end of which is engaged in a retaining lug provided on the main gripping element.

10 13. A safety device according to any one of Claims 7 to 12 wherein the main gripping element is in the form of a cylindrical housing, and the moveable gripping element has inclined resiliently mounted walls to engage the exterior of the cylindrical main gripping element.

15 14. A safety device substantially as herein described with reference to and as shown in Figures 1 to 3 of the accompanying drawings.

15. A safety device substantially as herein described with reference to and as shown in Figures 1 to 5 of the accompanying drawings.

20

16. A safety device substantially as herein described with reference to and as shown in Figures 6 and 7 of the accompanying drawings.

17. A safety device substantially as herein described with reference to and as
25 shown in Figure 8 of the accompanying drawings.

18. Any novel feature or combination of features disclosed herein.

ABSTRACT

5

“IMPROVEMENTS IN OR RELATING TO A SAFETY DEVICE”

10

A safety device is disclosed which is configured to be actuated by the supply of gas. The safety device incorporates an outlet vent pipe (13, 21) which is sealed by a releasable clip (1). The releasable clip has a first elongate main gripping element (2) and a second elongate moveable gripping element (8). The main gripping element has a retaining element (3) to retain one end (10) of the moveable gripping element (8). The safety device also includes an arrangement to retain the other end of the moveable gripping element (8) in a predetermined position such that the clip (1) may grip a fabric tube or the like between the main gripping element (2) and the moveable gripping element (8). A mechanism is provided which responds to a supply signal to move said other end of the moveable gripping element to release the grip.

15

20




FIG 2




FIG 3





FIG 1

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)




FIG 6




FIG 7

THIS PAGE BLANK




FIG. 8

THIS PAGE BLANK (USPTO)